

A fundamental theory of the ...

S/281/63/000/001/004/004
E194/E155

discharge from the pump to the total drive power. Separate expressions are derived for such components of the equation as the hydraulic efficiency, the frictional head and others, so that the resulting equation for pump performance is complicated though usable. Analysis of the expressions derived shows that there is an optimum value of fluid friction against the disk which gives maximum pump efficiency. In practice, the best results are obtained if the disk sections fill 0.4-0.5 of the inlet section. The influence of pump design and geometry on performance is then considered and performance curves are constructed for pumps of given designs. A special rig was built in which the spacing between disks could be in the range 5 - 9 mm, the coefficient of friction 0.032 - 0.77, the speed 1000 - 7000 rpm, the discharge diameter 100 - 500 mm, and the height of roughnesses on the disk surface (which influences the Reynolds number in the gap) 0.005 - 0.85 mm. There is good agreement between experimental characteristics obtained on this rig and calculated values, provided that the specific speed is greater than 70 - 80. If it is less, the experimental values of efficiency and head are lower than calculated. There are 12 figures.

Card 2/2

SUBMITTED: July 6, 1961

PHASE I BOOK EXPLOITATION

SOV/6204

Perel'man, Roman Grigor'yevich

Dvigateli galakticheskikh korabley (Engines for Intergalactic Ships) Moscow, Izd-vo AN SSSR, 1962. 197 p. (Series: Akademiya nauk SSSR. Nauchno-populyarnaya seriya) Errata slip inserted. 25,000 copies printed.

Sponsoring Agency: Akademiya nauk SSSR.

Resp. Ed.: K. P. Stanyukovich; Ed. of Publishing House: N. B. Prokof'yeva; Tech. Ed.: S. P. Golub'.

PURPOSE: This book is a popular treatment intended to acquaint nonspecialist readers with various engine design concepts for use in intergalactic ships.

COVERAGE: The book gives information on interstellar "routes", discusses the principal limitations of rockets with engines using chemical and nuclear fuels, and presents the basic concepts necessary to an understanding of

Card 1/2

PHASE I BOOK EXPLOITATION

SOV/5703

Perel'man, Roman Grigor'yevich, Candidate of Technical Sciences

Shturm kosmosa prodolzhayetsya (The Assault on Space Continues) Moscow, Izd-vo "Znaniye," 1961. 44 p. (Series: Vsesoyuznoye obshchestvo po rasprostraneniyu politicheskikh i nauchnykh znaniy. Seriya IX, 1961: Fizika i khimiya, no. 13) 26,000 copies printed.

Ed.: I. B. Faynboym; Tech. Ed.: A. S. Nazarova.

PURPOSE: This booklet is intended for the general reader.

COVERAGE: The booklet reviews the development of Soviet exploration of outer space and describes aspects of recent Soviet achievements. Propulsive efficiencies, velocity requirements, rockets, guided rocket vehicles, satellites, the satellite capsule, launching, control, power systems, and atmospheric entry are discussed. References to future possibilities and trends are made throughout the booklet. A few illustrations are included. No personalities are mentioned. There are 26 references, all Soviet.

Card 1/2

PEREL'MAN, Roman Grigor'ievich; STANYUKOVICH, K.P., prof., otv. red.;
PROKOF'YEVA, N.B., red. izd-va; GOLUB', S.P., tekhn. red.

[Engines of galactic ships] Dvigateli galakticheskikh korablei.
Moskva, Izd-vo Akad. nauk SSSR, 1962. 197 p. (MIRA 15:9)
(Spaceships--Propulsion systems)

PEREL'MAN, Roman Grigor'yevich, kand. tekhn. nauk; FAYNBOYM, I.B., red.;
NAZAROVA, A.S., tekhn. red.

[Assault on outer space continues] Shturm kosmosa prodolzhaetsia.
Moskva, Izd-vo "Znanie," 1961. 44 p. (Vsesoyuznoe obshchestvo po
rasprostraneniю politicheskikh i nauchnykh znaniy. Ser.9, Fizika
i khimiya, no.13) (MIRA 14:8)

(Space flight)

PHASE I BOOK EXPLOITATION

SOV/5686

Perel'man, Roman Grigor'yevich

Zvezdnyye korabli (Stellar Ships) Moscow, Izd-vo "Sovetskaya Rossiya," 1961.
61 p. 20,000 copies printed.

Scientific Ed.: G. I. Babat, Doctor of Technical Sciences, Professor;
Ed.: N. Ts. Stepanyan; Ed.: E. Rozen.

PURPOSE: This is a popular booklet for general readers.

COVERAGE: The booklet deals with problems in the development of astronautics. Prognosis for the future and the scientific basis for building spaceships are given on the assumption that the development of astronautics will follow the lines being laid down by science at the present time. Soviet and non-Soviet open sources were used. No personalities are mentioned. There are no references.

Card 1/3

PERELMAN, R., STANYUKOVICH, K.

Let's be optimistic! Znan.sila 35 no.7:38-40 J1 '60.

(Space flight)

(MIRA 13:7)

Perel'man, R.G.

S/024/60/000/04/003/013

E/194/E484

82207

10.4000

AUTHOR: Perel'man, R.G. (Moscow)

TITLE: The Selection of Optimum Parameters for an Injector-
Pump Runner System

PERIODICAL: ³Izvestiya Akademii nauk SSSR, Otdeleniye tekhnicheskikh
nauk, Energetika i avtomatika, 1960, No.4, pp.59-73

TEXT: The method developed by TsAGI (Central Aerodynamic and Hydrodynamic Institute) for the design of fans can be adapted to determine the optimum inlet diameter of a pump runner to achieve minimum inlet pressure loss. This makes approximate allowance for rotary motion that is set up in fluid that has not yet reached the runner. The anti-cavitation properties of the equipment may be further improved by means of an ejector, such as that illustrated schematically in Fig.1, in which part of the head available before the nozzles is used to set up axial flow and for ejection, and another part to set up rotary motion of the fluid before entering the runner. The fluid for the ejector is taken from the high-pressure part of the system. The object of the Present article is to determine the optimum distribution of the head available before the nozzle of the ejector to set up axial

Card 1/6

23

X

S/024/60/000/04/003/013

E194/E484 82207

The Selection of Optimum Parameters for an Injector-Pump Runner System

and peripheral velocity in the ejector-pump system. The angle of the nozzle in the horizontal plane β_2 in Fig.1 is first considered. Tests have shown that for small values of β_2 the flow rotates mainly near the chamber walls, but when $\beta_2 = 45^\circ$ the rotary motion is reasonably well distributed. On the other hand, increase of β_2 above 45° reduces the rotary rate of flow. Experimentally determined values of the two velocity components for different values of β_2 are plotted in Fig.2, and Fig.3 shows velocity diagrams across the radius for three different values of β_2 . It is seen that a value of β_2 close to 45° is the most favourable. The generally accepted equation for determination of the head required at inlet to the set (in the absence of an ejector) drawn up for flow conditions on the outer diameter of the blades, where cavitation is most likely, is given in Eq.(2). The ejector-pump system is then analysed further to derive the necessary changes in Eq.(2), and the optimum inlet diameter in the presence of a shaft is given by Eq.(4), or in the absence of a shaft by Eq.(4'). The use of an ejector which sets up an additional head and rotates the

Card 2/6

S/024/60/000/04/003/013
E194/E484 82207

The Selection of Optimum Parameters for an Injector-Pump Runner System

flow causes changes in the expression for determining the total inlet head, see Eq.(2'). Further consideration is then given to detailed consideration of terms entering into Eq.(2). The reduction in required pressure that results from reduction in the relative velocity at the inlet diameter is assessed. The change in angle of attack resulting from the rotation of the flow before the wheel is discussed in relation with the vector diagram of Fig.4. Expression (12) is derived for the increase in the available static head caused by the ejectors. The equation for the optimum head distribution is then derived in the form of Eq.(15) which may be used to derive various of the necessary velocities. Analytical solution of Eq.(15) involves the use of a small difference between two large terms and great care is required to obtain sufficient accuracy and accordingly a semi-graphical method is recommended. The semi-graphical method gives graphs in dimensionless coordinates for the common practical case of an overhung wheel. The construction and use of the graph is illustrated by an example of selection of the angle of slope of

Card 3/6

✓

S/024/60/000/04/003/013
E194/E484 82207

The Selection of Optimum Parameters for an Injector-Pump Runner System

the ejector nozzles. The nature of the changes of the various magnitudes (see Eq.(13)) with constant drop in the nozzle and various angles of slope of nozzle are plotted in Fig.5 and curves of the relative gain in inlet pressure are plotted in Fig.6. Finally, Fig.7 shows a combined resultant graph of the relative gain in inlet pressure, which may be used directly to determine the best ejector nozzle angle. The use of this graph is explained and numerical examples are worked, see Fig.8, curve 2. It is shown from Fig.7 that in one particular case the improvement in anti-cavitation properties of the pump which can be achieved by using a combined ejector is about 1.2 times greater than that when all the pressure drop on the nozzle of the ejector is used to set up swirl. At present, axial ejector-pumps are commonly used and accordingly an example is given. The combined resultant gain curves for this case are given in Fig.9. Experimental work was done using an incompressible liquid to check the above recommendations on the selection of optimum nozzle angles for the ejector in the ejector pump system. The necessary

Card 4/6

S/024/60/000/04/003/013

E194/E484 82207

The Selection of Optimum Parameters for an Injector-Pump Runner System

pump design data are given. The procedure used to determine the cavitation characteristics is explained. A cross-sectional diagram of the pump and ejector are shown in Fig.11. Results are plotted in Fig.10 and it will be seen that, for reasons which are explained, the increase in static pressure developed by the ejector was about 5% lower than the calculated figure. There was a corresponding diminution in the possible gain. Finally, the combined ejector illustrated in Fig.11b was tested. In this case, the possible reduction in the dynamic component of the pressure required at inlet was 5 to 6% below the calculated value, for reasons which are explained. In selecting the optimum pump inlet diameter, and so in constructing the graphs of Fig.7 and 9, no allowance was made for possible further increase in optimum diameter caused by swirl of the liquid before inlet to the runner. This simplifies the problem but to be sure that the assumptions do not greatly impair the advantages of using an ejector, an assessment is made of the change in optimum diameter that results from allowing for swirl of the liquid. The results

Card 5/6

X

PERELMAN, R. G.

10(2)(4); 14(6)(10) PHASE I BOOK EXPLOITATION SOV/3427

Polikovskiy, Vladimir Isaakovich and Roman Grigor'yevich Perel'man

Voronkoobrazovaniye v zhidkosti s otkrytoy poverkhnost'yu (Formation of Funnel-Shaped Depressions in Liquid with a Free Surface)
Moscow, Gosenergoizdat, 1959. 190 p. 1,750 copies printed.

Ed.: P.G. Kiselev; Tech. Ed.: G.Ye. Larionov.

PURPOSE: This book is intended for specialists and students of hydrotechnics, as well as for engineers designing various kinds of industrial and transportation hydraulic system.

COVERAGE: This book presents the results of theoretical and experimental studies devoted to the problem of vortex formation in the flow of a liquid with a free surface. The book is divided into two main parts. The first part discusses the physical nature of vortices and the method of evaluating phenomena which arise when a liquid has a vortex. Among the topics considered are: theory of vortex formation, experimental study of physical

Card 1/6

Formation of Funnel-Shaped (Cont.)

SOV/3427

existence of vortex formation, and calculation and construction of vortex profiles. Part two discusses vortex formation in the upper water of hydrotechnical installations. Among the topics considered are: vortex formation in front of locks of hydrotechnical installations, determination of lock stresses in draining off solid floating objects by means of vortices, evaluation of permeability capacity of hydroturbine spiral chambers, prevention of vortex formation, and the use of vortices in cleaning foreign objects from the surface of reservoir waters. There are 130 references: 113 Soviet, 6 German, 5 English, 3 French, 1 Hungarian, 1 Italian, and 1 Rumanian.

TABLE OF CONTENTS:

Preface	5
PART ONE. THEORY OF PHYSICAL EXISTENCE AND METHODOLOGY OF EVALUATING PHENOMENA OF A LIQUID DURING VORTEX FORMATION	
Ch. I. Theory of Vortex Formation	7
1. Causes and physical nature of the phenomenon of vortex formation	7
Card 2/6	

Formation of Funnel-Shaped (Cont.)

SOV/3427

2. Escape of a liquid with non-rotating vortex through a bottom orifice and the critical state of flow	13
3. Theory of steady vortex formation	18
Ch. II. Experimental Study of the Physical Nature of Vortex Formation	
4. Basic experimental equipment	39
5. Evaluation of the effect of viscosity, discharge of liquid, disturbing moments, and pressure on vortex formation	39
6. Modelling of vortex formation	41
7. Determination of discharge coefficients during escape through a circular bottom orifice with a vortex over it	46
8. Approximate value of the possibility of a vortex break in a bottom orifice	49
9. Experiments on the prevention of vortex formation in a cylindrical tank during escape through a bottom orifice	53
10. Vortex formation in a side discharge	55
11. Draining of solid floating bodies by vortices	61
	70
Ch. III. Master Calculations and Construction	76
Card 3/6	

Formation of Funnel-Shaped (Cont.)

SOV/3427

- | | |
|---|----|
| 12. Determination of calculation coefficients | 76 |
| 13. Methodology of constructing the calculation profile of a vortex | 83 |
| 14. Numerical example of constructing a vortex profile | 86 |

PART TWO. VORTEX FORMATION IN UPPER
WATER OF HYDROTECHNICAL INSTALLATIONS

Ch. IV. Vortex Formation in Front of Locks of Hydrotechnical Installations.

- | | |
|--|-----|
| 15. General considerations on the causes of formation of vortices and their intensity depending on the elevation of the lock | |
| 16. Approximate construction of the form of the flow surface before the lock | 91 |
| 17. Quantitative evaluation of the intensity of the vortex before a lock. Examples of calculation of vortices | 95 |
| 18. Experimental determination of the distance of a vortex from lock on a model and in actual practice | 98 |
| | 103 |

Card 4/ 6

Formation of Funnel-Shaped (Cont.)

SOV/3427

19. Observations in actual practice of spontaneous vortex formation and the effect of draining solid floating bodies by vortices	103
Ch. V. Determination of Stresses on Locks in the Draining of Solid Floating Bodies (logs) by Vortices	106
20. Preliminary considerations	106
21. Results of observations and characteristic cases of calculation	109
22. Determination of the impact force of a solid body on the lock (case A-1)	113
23. Determination of stress on the lower edge of a lock (case B-2)	116
24. Examples of calculating additional stresses on locks	119
Ch. VI. Evaluation of Permeability Capacity of Spiral Chambers of Hydroturbines	122
25. General considerations	122
26. Maximal discharge during escape in the form of a developed vortex	128

Card 5/6

Formation of Vortex	
27. Maximum discharge during flood level has a determining effect	137
28. Maximum discharge during stage in the form of overflow	143
Ch. VII. Prevention of formation of vortices	
29. Prevention of vortex formation near water intakes (in hydraulic dam, in main pipe, in front of locks, etc.)	155
Ch. VIII. Prevention of vortex formation in the vicinity of locks	
30. Hydraulic characteristics of locks and vortices and their transmission	164
31. Use of vortices for the removal of sludge, ice, and debris	174
32. Control of vortex formation during the formation	173
Bibliography	183
AVAILABLE: Library of Congress	186

Card 6 6

AC/jb
4-8-60

SOV/25-59-6-27/49

AUTHOR: Perel'man, R.G., Candidate of Technical Sciences

TITLE: The Attack on the Thermal Barrier

PERIODICAL: Nauka i zhizn', 1959, Nr 6, pp 59-64 and p 3 of centerfold (USSR)

ABSTRACT: This is a popular introduction into the problems connected with the attempt to overcome the so called thermal barrier, i.e. the sharp increase in heating up of the aircraft during flight, and the increasing difficulties connected with building high speed aircraft. The author deals first with the sound barrier and how it was overcome, and then describes an imagined flight of 4,500 km/h at a height of 11 km. He sets forth the difficulties arising because of the intensive heating up of the aircraft, stating that a further rise in speed will require the increased use of heat-resistant steels. It will also be necessary to develop new methods and instruments for the processing of materials in order to ensure the high productivity of the aircraft industry with such steels. It is evident that the materials selected for

Card 1/3

SOV/25-59-6-27/49

The Attack on the Thermal Barrier

the building of aircraft should be as little as possible subjected to dimensional changes due to temperature. The author refers to the US experimental aircraft "X-15" designed for training flights at super-sonic speeds. However, the selection of suitable construction materials does not solve the entire problem since the aircraft also holds tanks with fuel, numerous devices and a human being. The difficulties experienced in this connection are also set forth. The author deals with the possibilities of "keeping off" the heat by making a "sweating" skin of porous, non-rusting steel. The author also mentions other known methods leading to a protection of the skin against high temperatures, such as a skin of materials which only poorly conduct heat, are fireproof, or let the hot air rotate the turbine wheel of a special refrigerator. Examining the prospects for the future, the author points to the possibility of maneuvering, i.e. to fly at a maximum speed until the aircraft skin is heated up to about 400° C, then reduce the speed radically to let the aircraft cool off and thereafter increase the speed again. He hints at increas-

Card 2/3

SOV/25-59-6-27/49

The Attack on the Thermal Barrier

ing the aircraft's altitude as another way of meeting the difficulty. It will permit the aeroplane to fly at a speed of about 10,000 km/h at heights of 100 to 150 km for several hours without overheating. Concluding, he states that through the endeavors of engineers, designers, physicists and chemists aircraft will from year to year be able to fly faster, farther and higher. There are 11 sets of drawings and 1 graph.

Card 3/3

PEREL' MAI, N.G., kand. tekhn. nauk

Nuclear transport. Politekh. obuch. no. 6:66-79 Je '57.
(MIRA 12:4)

(Nuclear engineering)

KOVALEVSKAYA, A.Ye. PEREL'MAN, R.G. (Moskva).

Heat exchange in the field of action of centrifugal forces.
Izv. AN SSSR. Otd. tekhn. nauk. no.11:92-94 N '58.

(MIRA 12:1)

(Heat--Transmission) (Centrifugal force)

SOV/124-57-9-10349

Translation from: Referativnyy zhurnal, Mekhanika, 1957, Nr 9, p 66 (USSR)

AUTHORS: Polikovskiy, V. I., Perel'man, R. G.

TITLE: The Evaluation of Loads on Water Gates Due to Floating Solid Bodies Sucked Into Whirlpools (Otsenka nagruzok na zatvory pri podsasyvanií voronkami tverdykh plavayushchikh tel)

PERIODICAL: Tr. MAI, 1955, Nr 50, pp 216-230

ABSTRACT: The paper submits the results of investigations on the evaluation of possible additional loads on water gates due to solid floating bodies (logs) sucked under by whirlpools. The investigations were conducted in the hydraulic flume on a model of the spillway dam of the Kuybyshev Hydraulic Power Plant built to a scale of 1:50. Whirlpools were created in the corners between the gate and the pier by means of a tangential delivery of water through an eddy stimulator. The basic laboratory tests were made with two values of the opening of the gate $a/H=0.25 + 0.30$ and 0.5. The Reynolds number was expressed as $R = rC_u/\gamma$, where C_u was the peripheral velocity at a radius r . Round wooden logs were used as models of the floating bodies. A high-speed motion-picture film was made at 80 frames per second. —The

Card 1/3

SOV/124-57-9-10349

The Evaluation of Loads on Water Gates Due to Floating Solid Bodies (cont.)

tests were analyzed by the consecutive projection onto a screen of the single motion-picture frames and the positioning of the moving body upon a coordinate grid every 1/80 of a second. Floats entering in the hollow of a vortex and observed by means of a stroboscope, as well as on the coordinate grid, made possible an evaluation of the intensity of the whirlpool. The authors also conducted full-scale observations on the suction of floating objects into the whirlpool under the water gates of the Ivan'kovskaya dam. On the basis of the investigations made, as well as of investigations made by other authors, two typical cases of the motion of a log before a gate were established: A) When the whirlpool does not have the intensity required for sucking a body under the gate, and B) when the whirlpool sucks the body under and carries it out under the gate. In the first case (direct impact of the log against the gate), assuming that the impact is absolutely inelastic, the impulse of the force is determined as equal to $N = 0.8mv$ with $\alpha = 45^\circ$ and $N = mv$ with $\alpha = 0^\circ$ and 90° , where α is the angle between the direction of the log and the normal to the gate. Since the greatest specific impact loads occur with $\alpha = 0^\circ$ (head-on longitudinal impact by the log), this impact condition is the most dangerous. In this load condition the mean value of the force during the time of the impact is

Card 2/3

$$P = \frac{N}{\tau} = \frac{mv}{2\sqrt{3}\gamma_T/E_g}$$

SOV/124-57-9-10349

The Evaluation of Loads on Water Gates Due to Floating Solid Bodies (cont.)

In the second case, if the log, because of its large size and an insufficient intensity of the whirlpool, is not carried away by the latter at once, but rotates vertically, goes down along the gate, and accomplishes a turn around the bottom edge of the gate, then the force acting upon that edge is determined by the expression

$$N = 0.5 c_x \rho s v^2 = 0.5 c_x \rho (l-h) D v^2$$

At the end of the article two examples of design calculations are given. The authors did not analyze the significance of the described load on the gate in comparison with the design load (hydrostatic pressure). Bibliography: 9 references.

A. P. Berezinskiy

Card 3/3

SOV/24-58-10-30/34

AUTHORS: Perel'man, R. G., Polikovskiy, V. I. (Moscow)

TITLE: Hydraulic Impedance of Rectilinear Channels in the Field of Centrifugal Forces (Gidravlicheskiye soprotivleniya pryamolineynykh kanalov v pole tsentrobezhnykh sil)

PERIODICAL: Izvestiya Akademii nauk SSSR, Otdeleniye tekhnicheskikh nauk, 1958, Nr 10, pp 150-153 (USSR).

ABSTRACT: A determination was carried out of the hydraulic impedance of smooth brass tubes whose internal diameter was 10, 20 and 28 mm. The tubes were placed radially in a plane which was at right angles to the axis of rotation. Experiments were carried out in air up to Reynolds numbers $R = 7 \times 10^{-2}$. The experimental results are shown in Fig.1, in which the frictional loss coefficient λ is plotted as a function of R and the angular speed n . An expression is derived which gives the hydraulic impedance as a function of the parameters of the tube and the rate of revolution (Eq.6). There are 4 figures and 7 references of which 3 are German and 4 Soviet.

SUBMITTED: July 27, 1957.

Card 1/1

PHASE I BOOK EXPLOITATION

527

Perel'man, Roman Grigor'yevich, Candidate of Technical Sciences

Yadernyye dvigateli (Nuclear Engines) Moscow, Izd-vo "Znaniye", 1958. 54 p.

(Series: Vsesoyuznoye obshchestvo po rasprostraneniyu politicheskikh i nauchnykh znaniy. Seriya IV, 1958, no. 4 and 5) 60,000 copies printed.

Scientific Ed.: Nikolayev, N. A.; Ed. of Publishing House: Lanina, L. I.;
Tech. Ed.: Streletskiy, I. A.

PURPOSE: The booklet is intended for the general public interested in future developments in the field of atomic energy.

COVERAGE: The author describes in popular language the prospects for utilizing atomic energy, particularly in the field of transportation. No precise description of transportation facilities in the atomic era can as yet be given. The Soviet Union has accumulated considerable experience in the continuous operation of industrial nuclear electric power plants. The Sixth Five Year Plan calls for new nuclear engines and new larger electric power plants, and nuclear ice-breakers, one of which is now almost completed. The author describes the advantages of installations of power plants operating on nuclear fuel. He cites as

Card 1/4

Nuclear Engines

527

an example the recent Soviet achievement in launching December 5, 1957 on the River Neva the nuclear icebreaker "Lenin", which is 134 m. long, 27.6 m. wide, 16 m. high, and has a 16,000 ton displacement and a speed of more than 30 km. per hour. The icebreaker is equipped with launches on its deck and a helicopter on a special platform. Its nuclear engine produces more than 40,000 horsepower. The potential designs of ram jets operating on nuclear fuel are under study, i.e., the VRD (Jets) and the TRD (Turbojets). The future will bring nuclear space ships and the use of controlled thermonuclear reactions. The discovery of a method for controlled transformation of matter into energy in quantum engines will open new cosmic perspectives in rocket technique. Photon and ion rockets will be used in the future. V.V. Zvonkov, Corresponding Member of the USSR Academy of Sciences, is mentioned as the person who supervised the work on nuclear-powered tankers of 15,000 hp. There are 23 references, of which 18 are Soviet, 4 English.

Card 2/4

Nuclear Engines

527

TABLE OF
CONTENTS:

The Engine of the Future	3
Across the Nine Seas	10
Eighty Thousand Kilometers Under Water	17
The Locomotive of Deserts, Distant Roads, and Mountain Passes	21
On the Highway of the Atomic Era	29
Around the World	31
The Atom Acquires Wings	38
Nuclear Rockets	42

Card 3/4

Nuclear Engines

527

Conclusion

53

Bibliography

54

AVAILABLE: Library of Congress

Card 4/4

IS/eag

9/25/58

SOV/24-58-11-21/42
AUTHORS: Kovalevskaya, A. Ye. and Perel'man, R. G. (Moscow)
TITLE: On the Heat Exchange in a Field Affected by Centrifugal Forces (O teploobmene v pole deystviya tsentrobezhnykh sil)
PERIODICAL: Izvestiya Akademii Nauk SSSR, Otdeleniye Tekhnicheskikh Nauk, 1958, Nr 11, pp 92-94 (USSR)
ABSTRACT: M. A. Mikheyev (Refs 1 and 2) studied the heat release from heated rotating rods to the atmosphere (external problem). In earlier work (Ref 3) the authors of this paper studied the heat flow inside a canal (internal problem). The investigations described in this paper are based mainly on the results of this earlier work and relate to determining the hydraulic resistance of straight canals inside a field affected by centrifugal forces. Various authors have published formulae enabling inter-relation in the first approximation of the heat transfer coefficient α and the Nusselt number N_{Nu} . The possibility of using the relations published by Ludwig (Ref 4) and Kutateladze (Ref 5) (Eqs. 1 and 2 of this paper) are determined by the extent to which the heat propagates in the flow along the investigated section. In the experiments carried out by the authors of this paper the

Card 1/3

SOV/24-58-11-21/42

On the Heat Exchange in a Field Affected by Centrifugal Forces

length of the ring section in which the heat transfer was effected consisted altogether of two tube sizes and it can be anticipated, therefore, that the experimental results in the investigated region and the applied length of the heated section will be intermediate relative to those calculated according to the formulae of Ludwig and of Kutateladze. A sketch of the used experimental set-up is shown in Fig.3. It was found that the experimental results are in satisfactory agreement with the theoretical relations plotted according to the formulae of Ludwig and Kutateladze. It can be seen from the graph, Fig.2 that an absolute decrease in the flow rate, i.e. of the N_{Re} criterion, will bring about an increase in the difference between the experimentally and the theoretically determined values and the experimentally obtained coefficients will be larger than the calculated values. This is possible due to the relative increase in the intensity of the secondary flows in the case of

Card2/3

SOV/24-58-11-21/42

On the Heat Exchange in a Field Affected by Centrifugal Forces

decreasing values of the ratio N_{Re} to N'_{Re} .

There are 3 figures and 5 references, 4 of which are Soviet, 1 German.

SUBMITTED: December 31, 1957

Card3/3

PEHEL'MAN, R.G., kand.tekhn.nauk

Motors for Galactic ships. Nauka i zhizn' 25 no.7:60-64 J1 '58.
(Space flight) (MIRA 11:9)

124-57-1-531

Translation from: Referativnyy zhurnal, Mekhanika, 1957, Nr 1, p 66 (USSR)

AUTHOR: Perel'man, R. G.

TITLE: Investigation of the Phenomenon of Funnel Formation (Issledovaniye yavleniya voronkoobrazovaniya)

PERIODICAL: Tr. MAI, 1954, Nr 38, pp 100-149

ABSTRACT: The study is devoted to the problem of the formation of a funnel during the outflow of a liquid from a cylindrical container through a circular opening in its horizontal bottom. In the experimental apparatus the funnel was artificially created by means of a whirling motion produced by concentrated jets which were tangentially injected into the container. In his examination of the motion during the stationary outflow of a viscous liquid, the author assumes that part of the head is expended in the maintenance of the whirling motion of the viscous liquid, and that only the remainder of the head is expended "in producing the discharge." The autho. assumes the following law for the distribution of the peripheral velocities c_u in the flow of the whirling viscous liquid:

Card 1/2

$$r^x c_u = \text{const},$$

124-57-1-531

Investigation of the Phenomenon of (cont.)

where r is a radius and x is a head-loss coefficient comprising the energy losses due to internal friction and the friction with the walls and bottom of the container. This coefficient is determined experimentally. The author also proposes a formula for the approximate calculation of the pressure distribution in the presence of a funnel. Regarding model tests of the formation of a funnel, the author concludes that the determining influence therein is exerted by the viscosity; hence model tests must conserve the Reynolds number, which is expressed as follows: $R = r c_u / \nu$. The determination of the discharge coefficient in the presence of a funnel is also examined. In conclusion a numerical example of the tracing of a funnel profile is set forth.

Bibliography: 7 references

O. F. Vasil'yev, N. A. Pritvits

1. Liquids--Flow--Analysis

Card 2/2

SOV-25-58-7-33/56

AUTHOR: Perel'man, R.G., Candidate of Technical Sciences
TITLE: ~~A Window to the Future~~ (Okno v budushcheye). The Engines
of Spaceships (Dvigateli galakticheskikh korabley).
PERIODICAL: Nauka i zhizn', 1958, Nr 7, pp 60 - 64 and p 3 of inner fold.
(USSR)
ABSTRACT: Fiction. There are 4 drawings.
1. Spaceships--Propulsion

Card 1/1

SITSEYN, L.B. (Leningrad); PEREL'MAN, R.L., professor, zaveduyushchiy; SEMENOV, A.D. dotsent, direktor.

Studies on the active tonus of the lungs with simultaneous bilateral water manometry. Arkh.pat. 15 no.2:45-50 Ja-P '53. (MLRA 6:5)

1. Otdel eksperimental'noy patologii Leningradskogo tuberkuleznogo instituta im. A.Ya. Shternberga (for Perel'man). 2. Leningradskiy tuberkuleznyy institut im. A.Ya. Shternberga (for Semenov). (lungs)

SHUTSKAYA, Ye.I., kand. med. nauk; Prinsipali uchastiye: RABINOVICH, S.Ye., prof.; SLEPTSOVA, A.I., vrach; LIVEN, K.I., vrach; SOKOLOVA, R.I., vrach; PEREL'MAN, R.M., vrach; AL'TMAN, I.M., vrach; SHEPILOV, N.S., kand. veterin. nauk; SVIRIDOV, A.A.

Epidemiological importance of tuberculosis in cattle.
Veterinariia 40 no.10:19-20 0'63. (MIRA 17:5)

1. Novosibirskiy nauchno-issledovatel'skiy institut tuberkuleza
(all except Shepilov, Sviridov).

CHEREMNYKH, L.P., kand.med.nauk; PEREL'MAN, R.M.

Clinicomorphological comparisons in chronic primary tuberculosis of
the lungs in children. Probl. tub. no.2:74-79 '64.

(MIRA 17:12)

1. Novosibirskiy nauchno-issledovatel'skiy institut tuberkuleza
(dir. M.V.Svirezhev).

FEOFILOV, G.L.; PEREL'MAN, R.M.; KHRAMOVA, L.P.

Bronchological examination of children with chronic pulmonary tuberculosis. Probl. tub. 42 no.1:16-21 '64. (MIRA 17:8)

1. Institut eksperimental'noy biologii i meditsiny (dir. Yu.I. Borodin) Ministerstva zdravookhraneniya RSFSR i Novosibirskiy nauchno-issledovatel'skiy institut tuberkuleza (dir. M.V. S Svirzhev).

PEREL'MAN, R.S.

Azerbaijan State Medical Library of the Ministry of Public Health
of the Azerbaijan S.S.R. Azerb. med. zhur. no.11:71-73 H '60.
(MIRA 13:12)

1. Ispolnyayushchiy obyazannosti direktora Azerbaydzhanskoy gosudar-
stvennoy nauchnoy meditsinskoy biblioteki Ministerstva zdravookhraneniya
Azerbaydzhanskoy SSR.

(AZERBAIJAN—MEDICAL LIBRARIES)

1ST AND 2ND COPIES										3RD AND 4TH COPIES									
PROCESSES AND PROPERTIES INDEX																			
<p>2A</p> <p>Problems in the production of ammonium nitrate and ammonium sulfate. S. Petrucci and V. Klevke. J. Chem. Ind. (U. S. S. R.) 17, No. 1, 28 31 (1940). --Appl is discussed. Caking of NH_4NO_3 can be prevented by drying the crystals below 32°. H. M. Leicester</p>																			
<p>ADD-556 METALLURGICAL LITERATURE CLASSIFICATION</p>																			
FROM SYNDICATE										FROM DOMESTIC									
180000-2										180000-117 ONLY 001									
180000-2										180000-117 ONLY 001									

18

CA

PROCESSES AND PROPERTIES INDEX

The conversion of gypsum by solutions of ammonium carbonates. S. Perelman and V. Rozer. *J. Chem. Ind. (Moscow)* 1935, No. 17, 28-37. — An excess of 5% of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ is treated with a 40% soln. of $(\text{NH}_4)_2\text{CO}_3$ at 40-60°. If the reagents are mixed slowly and equally, the ppt. of CaCO_3 filters well and requires little washing. The reaction is complete in 1.5-2 hrs. The filtrate contains 0.2% free NH_3 , which is neutralized by H_2SO_4 . The yields of CaCO_3 and $(\text{NH}_4)_2\text{SO}_4$ are 92.3 and 96.8%. The CaCO_3 contains 17-20% H_2O , and when dry resp. The CaCO_3 contains 17-20% H_2O , and when dry gives a fine noncaking powder. If $2\text{CaSO}_4 \cdot \text{H}_2\text{O}$ or phos. gypsum is used in the reaction, a poor quality of CaCO_3 is obtained. H. M. Leicester

ASAC-31.4 METALLURGICAL LITERATURE CLASSIFICATION

1935-1936

1937-1938

1939-1940

1941-1942

1943-1944

1945-1946

1947-1948

1949-1950

1951-1952

1953-1954

1955-1956

1957-1958

1959-1960

1961-1962

1963-1964

1965-1966

1967-1968

1969-1970

1971-1972

1973-1974

1975-1976

1977-1978

1979-1980

1981-1982

1983-1984

1985-1986

1987-1988

1989-1990

1991-1992

1993-1994

1995-1996

1997-1998

1999-2000

2001-2002

2003-2004

2005-2006

2007-2008

2009-2010

2011-2012

2013-2014

2015-2016

2017-2018

2019-2020

2021-2022

2023-2024

2025-2026

2027-2028

2029-2030

2031-2032

2033-2034

2035-2036

2037-2038

2039-2040

2041-2042

2043-2044

2045-2046

2047-2048

2049-2050

2051-2052

2053-2054

2055-2056

2057-2058

2059-2060

2061-2062

2063-2064

2065-2066

2067-2068

2069-2070

2071-2072

2073-2074

2075-2076

2077-2078

2079-2080

2081-2082

2083-2084

2085-2086

2087-2088

2089-2090

2091-2092

2093-2094

2095-2096

2097-2098

2099-2100

2101-2102

2103-2104

2105-2106

2107-2108

2109-2110

2111-2112

2113-2114

2115-2116

2117-2118

2119-2120

2121-2122

2123-2124

2125-2126

2127-2128

2129-2130

2131-2132

2133-2134

2135-2136

2137-2138

2139-2140

2141-2142

2143-2144

2145-2146

2147-2148

2149-2150

2151-2152

2153-2154

2155-2156

2157-2158

2159-2160

2161-2162

2163-2164

2165-2166

2167-2168

2169-2170

2171-2172

2173-2174

2175-2176

2177-2178

2179-2180

2181-2182

2183-2184

2185-2186

2187-2188

2189-2190

2191-2192

2193-2194

2195-2196

2197-2198

2199-2200

2201-2202

2203-2204

2205-2206

2207-2208

2209-2210

2211-2212

2213-2214

2215-2216

2217-2218

2219-2220

2221-2222

2223-2224

2225-2226

2227-2228

2229-2230

2231-2232

2233-2234

2235-2236

2237-2238

2239-2240

2241-2242

2243-2244

2245-2246

2247-2248

2249-2250

2251-2252

2253-2254

2255-2256

2257-2258

2259-2260

2261-2262

2263-2264

2265-2266

2267-2268

2269-2270

2271-2272

2273-2274

2275-2276

2277-2278

2279-2280

2281-2282

2283-2284

2285-2286

2287-2288

2289-2290

2291-2292

2293-2294

2295-2296

2297-2298

2299-2300

2301-2302

2303-2304

2305-2306

2307-2308

2309-2310

2311-2312

2313-2314

2315-2316

2317-2318

2319-2320

2321-2322

2323-2324

2325-2326

2327-2328

2329-2330

2331-2332

2333-2334

2335-2336

2337-2338

2339-2340

2341-2342

2343-2344

2345-2346

2347-2348

2349-2350

2351-2352

2353-2354

2355-2356

2357-2358

2359-2360

2361-2362

2363-2364

2365-2366

2367-2368

2369-2370

2371-2372

2373-2374

2375-2376

2377-2378

2379-2380

2381-2382

2383-2384

2385-2386

2387-2388

2389-2390

2391-2392

2393-2394

2395-2396

2397-2398

2399-2400

2401-2402

2403-2404

2405-2406

2407-2408

2409-2410

2411-2412

2413-2414

2415-2416

2417-2418

2419-2420

2421-2422

2423-2424

2425-2426

2427-2428

2429-2430

2431-2432

2433-2434

2435-2436

2437-2438

2439-2440

2441-2442

2443-2444

2445-2446

2447-2448

2449-2450

2451-2452

2453-2454

2455-2456

2457-2458

2459-2460

2461-2462

2463-2464

2465-2466

2467-2468

2469-2470

2471-2472

2473-2474

2475-2476

2477-2478

2479-2480

2481-2482

2483-2484

2485-2486

2487-2488

2489-2490

2491-2492

2493-2494

2495-2496

2497-2498

2499-2500

2501-2502

2503-2504

2505-2506

2507-2508

2509-2510

2511-2512

2513-2514

2515-2516

2517-2518

2519-2520

2521-2522

2523-2524

2525-2526

2527-2528

2529-2530

2531-2532

2533-2534

2535-2536

2537-2538

2539-2540

2541-2542

2543-2544

2545-2546

2547-2548

2549-2550

2551-2552

2553-2554

2555-2556

2557-2558

2559-2560

2561-2562

2563-2564

2565-2566

2567-2568

2569-2570

2571-2572

2573-2574

2575-2576

2577-2578

2579-2580

2581-2582

2583-2584

2585-2586

2587-2588

2589-2590

2591-2592

2593-2594

2595-2596

2597-2598

2599-2600

2601-2602

2603-2604

2605-2606

2607-2608

2609-2610

2611-2612

2613-2614

2615-2616

2617-2618

2619-2620

2621-2622

2623-2624

2625-2626

2627-2628

2629-2630

2631-2632

2633-2634

2635-2636

2637-2638

2639-2640

2641-2642

2643-2644

2645-2646

2647-2648

2649-2650

2651-2652

2653-2654

2655-2656

2657-2658

2659-2660

2661-2662

2663-2664

2665-2666

2667-2668

2669-2670

2671-2672

2673-2674

2675-2676

2677-2678

2679-2680

2681-2682

2683-2684

2685-2686

2687-2688

2689-2690

2691-2692

2693-2694

2695-2696

2697-2698

2699-2700

2701-2702

2703-2704

2705-2706

2707-2708

2709-2710

2711-2712

2713-2714

2715-2716

2717-2718

2719-2720

2721-2722

2723-2724

2725-2726

2727-2728

2729-2730

2731-2732

2733-2734

2735-2736

2737-2738

2739-2740

2741-2742

2743-2744

2745-2746

2747-2748

2749-2750

2751-2752

2753-2754

2755-2756

2757-2758

2759-2760

2761-2762

2763-2764

2765-2766

2767-2768

2769-2770

2771-2772

2773-2774

2775-2776

2777-2778

2779-2780

2781-2782

2783-2784

2785-2786

2787-2788

2789-2790

2791-2792

2793-2794

2795-2796

2797-2798

2799-2800

2801-2802

2803-2804

2805-2806

2807-2808

2809-2810

2811-2812

2813-2814

2815-2816

2817-2818

2819-2820

2821-2822

2823-2824

2825-2826

2827-2828

2829-2830

2831-2832

2833-2834

2835-2836

2837-2838

2839-2840

2841-2842

2843-2844

2845-2846

2847-2848

2849-2850

2851-2852

2853-2854

2855-2856

2857-2858

2859-2860

2861-2862

2863-2864

2865-2866

2867-2868

2869-2870

2871-2872

2873-2874

2875-2876

2877-2878

2879-2880

2881-2882

2883-2884

2885-2886

2887-2888

2889-2890

2891-2892

2893-2894

2895-2896

2897-2898

2899-2900

2901-2902

2903-2904

2905-2906

2907-2908

2909-2910

2911-2912

2913-2914

2915-2916

2917-2918

2919-2920

2921-2922

2923-2924

2925-2926

2927-2928

2929-2930

2931-2932

2933-2934

2935-2936

2937-2938

2939-2940

2941-2942

2943-2944

2945-2946

2947-2948

2949-2950

2951-2952

2953-2954

2955-2956

2957-2958

2959-2960

2961-2962

2963-2964

2965-2966

2967-2968

2969-2970

2971-2972

2973-2974

2975-2976

2977-2978

2979-2980

2981-2982

2983-2984

2985-2986

2987-2988

2989-2990

2991-2992

2993-2994

2995-2996

2997-2998

2999-3000

6

CA

PROCESSING AND PREPARATION INDEX

The decomposition of Vyntka phosphorite by hydrochloric acid and the precipitation of the obtained phosphoric acid by limestone and milk of lime. I. Mirkin, S. Perej'man and I. Nihonova. *J. Chem. Ind. (Moscow)* 1933, No. 7, 56-62; cf. C. A. 23, 4050.— The full theoretical amt. of HCl must be used when this acid decomposes phosphorite. It is best to use 10% HCl soln., to avoid too much later washing. The phosphorite does not have to be finer than 20-mesh. Finely ground limestone will ppt. all the H_2PO_4 formed if sufficient time is allowed, but in practice it is best to end the neutralization with $Ca(OH)_2$. H. M. Leicester

AND SLA METALLURGICAL LITERATURE CLASSIFICATION

The alkaline absorption of nitrogen oxides. S. Paul
and I. Kantorovich. *J. Chem. Ind. (U. S. S. R.)*
17, No. 6, 3-9(1960).—Absorption of NO_x and N_2O de-
pends on time of contact of gas and soln. and on pressure.
At atm. pressure, oxidation of H_2O should be carried out
before absorption, but at 6 atm. the rate of the reaction is
so rapid that it does not hinder absorption of NO_x . In
 Na_2CO_3 solns., N_2O is absorbed faster than NO_x . These
solns. must contain at least 4 g. Na_2CO_3 per l. at 1 atm.
and 8-10 g. per l. at 6 atm. $\text{Ca}(\text{OH})_2$ solns. absorb
slightly faster than Na_2CO_3 solns., and suspensions of Ca-
 CO_3 absorb most slowly of all, but are economical to use
because of cheapness. When the d. of the absorbing solns.
is increased by the presence of large amts. of nitrate and
nitrite, the rate of absorption is lowered. Scrubbers are
more efficient for the absorption than is bubbling the gas
through the soln.
H. M. Leicester

PROCESS AND PROPERTIES INDEX																																																													
<p>DC</p> <p>DECOMPOSITION OF VYATKA PHOSPHORITE BY HYDRO- CHLORIC ACID, AND THE PREPARATION OF PHOSPHORIC ACID BY PRECIPITATION WITH CALCIUM CARBONATE OR MILK-OF-LIME. I. Mirkin, S. Paraleman, and I. Nikonov (J. Chem. Ind. Russ., 1933, 10, No. 7, 56--62). --96% extraction of H_3PO_4 is obtained by using sufficient 10% HCl to convert the entire Ca present into $CaCl_2$. The phosphorite (I) should be in the form of particles passing 20mesh. H_3PO_4 is pptd. by $Ca(OH)_2$ or $CaCO_3$ from the solution obtained after separation from insol. matter (II) (about 25% of the wt. of (I) taken). (II) settles very slowly, and is difficultly separated by filtration; the product obtained by pptn. of H_3PO_4 without previously eliminating (II) had a P_2O_5 content of 28%, as compared with 40% when (II) was absent, and only 70% of the P_2O_5 was assimilable. R. T.</p> <p>B-1-8</p>																																																													
<p>ASS-11-A METALLURGICAL LITERATURE CLASSIFICATION</p>																																																													
<table border="1"> <thead> <tr> <th colspan="10">SUBJECT INDEX</th> <th colspan="10">CLASSIFICATION</th> </tr> <tr> <th>1</th><th>2</th><th>3</th><th>4</th><th>5</th><th>6</th><th>7</th><th>8</th><th>9</th><th>10</th> <th>11</th><th>12</th><th>13</th><th>14</th><th>15</th><th>16</th><th>17</th><th>18</th><th>19</th><th>20</th> </tr> </thead> <tbody> <tr> <td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> <td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> </tbody> </table>		SUBJECT INDEX										CLASSIFICATION										1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20																				
SUBJECT INDEX										CLASSIFICATION																																																			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20																																										

1ST AND 2ND ORDER										3RD AND 4TH ORDER									
PROCESSES AND PROPERTIES INDEX																			
<p>ca</p> <p>The decomposition of Vysina phosphorite by hydrochloric acid and the precipitation of the obtained phosphoric acid by limestone and milk of lime. I. Mirkin, S. Ferrel'man and I. Nikonova. <i>J. Chem. Ind. (Moscow)</i> 1933, No. 7, 56-62; cf. C. A. 25, 4650. The full theoretical amt. of HCl must be used when this acid decomposes phosphorite. It is best to use 10% HCl soln. to avoid too much later washing. The phosphorite does not have to be finer than 20-mesh. Finely ground limestone will ppt. all the H_2PO_4 formed if sufficient time is allowed, but in practice it is best to end the neutralization with $Ca(OH)_2$. H. M. Leicester</p>																			
ASD-55A METALLURGICAL LITERATURE CLASSIFICATION																			
SECTION 1										SECTION 2									
SUBSECTION 1										SUBSECTION 2									
SUBSUBSECTION 1										SUBSUBSECTION 2									

127 AND 128 STREET

PROCESSED AND REPRODUCED

212 AND 4TH STREET

COMMON ELEMENT

COMMON VARIABLE

1

The crystallization of nitrogen-containing salts, ammonium sulfate and sodium nitrate. S. Paulmann and H. Kerschbaum. *J. Chem. Ind.* (U. S. S. R.) 18, No. 7, 26-31 (1958).—Large crystals of $(\text{NH}_4)_2\text{SO}_4$ are obtained by crystals from a solution in which the acidity does not exceed 1-3%. The presence of Fe_2O_3 in the solution causes formation of smaller crystals, but Fe_2O_3 has the opposite effect. Addition of H_3PO_4 improves the crystals, especially when Fe_2O_3 is present. Superphosphate and phosphoric acid have a similar effect if the acidity is low, but at higher acidities they give impure crystals. NaNO_3 crystals formed in neutral or acid solutions are larger and better formed than those from alkali solutions. The presence of NaCl and NaNO_2 in the solution has no effect on NaNO_3 crystals and Fe_2O_3 causes only a slight decrease in their size.

H. M. Leicester

ADD. 55.0 METALLURGICAL LITERATURE CLASSIFICATION

BOOK SYMBOLS

15 AND 128 STREET

COLLATION

BOOK SYMBOLS

15 AND 128 STREET

COLLATION

FEREL'MAN, S. L.

21995 FEREL'MAN, S. L. Fiziologicheskiy analiz danykh lobelinovoy proby pri opredelenii
vremeni krugoborota krvi. Vracheb. delo, 1949, No. 7, stb. 575-78.

SO: Letopis' Zhurnal'nykh Statey, No. 29, Moskva, 1949.

KARBUK, K.I.; PEREL'MAN, S.M.; PRAGER, I.A.; KHARLAKOV, V.A.

Proportional X-ray quantum counters and their use for X-ray
spectrum analysis. Izv.AN SSSR.Ser.fiz. 27 no.3:430-437 Mr
'63. (MIRA 16:2)

(X-ray spectroscopy)

BARONIN, V.N.; BETIN, Yu.P.; VERKHOVSKIY, B.I.; IVANOV, A.I.; PEREL'MAN, S.E.;
PRAGER, I.A.; KHARLAKOV, V.A.; SHELKOV, L.S.

Crystalless X-ray spectrometer with stabilization of the position
of the amplitude of the spectrum of a proportional counter. Zav.
lab. 30 no.4:498-500 '64. (MIRA 17:4)

1. Konstrukterskoye byuro "TSvetmetavtomatika".

S/048/63/027/003/023/025
B106/B238

AUTHORS: Narbutt, K. I., Perel'man, S. M., Prager, I. A.,
and Kharlakov, V. A.

TITLE: An attempt to use proportional counter tubes for
X-ray spectral analysis

PERIODICAL: Akademiya nauk SSSR. Izvestiya. Seriya fizicheskaya,
v. 27, no. 3, 1963, 430-437

TEXT: Two types of proportional counter tubes were tested, type 1 with its entry window in the side, and type 2 with a window in the support of the counter. All the windows were made of hermetic beryllium 150 - 200 μ thick. Type 1 instruments were filled with either argon, krypton or xenon, and in every case 10 % isopentane was added as an extinguisher. The anode filaments in type 2 were fixed straight to the support in order to reduce the dead space and the action of boundary effects on the amplitude resolution of the counter. The filling is a krypton-isopentane mixture at a pressure of 0.400 mm Hg. The electronic counting device is made up of a

Card 1/3

S/048/63/027/003/023/025
B106/B238

An attempt to use ...

pre-amplifier and a standard CCA (SSD) diffractometer counter unit. The amplitude distribution for characteristic K lines of various energies was studied under various conditions using a type 1 counter filled with argon. The mean pulse height was found to depend linearly on the quantum energy of the exciting radiation. The way in which the energy resolution of the instruments depends on the energy of the radiation to be recorded was also determined. The amplitude distribution of the fluorescent X-radiation was measured for the elements K to Cs in the periodic table using the three sorts of type 1 tube. In argon, a small argon loss peak occurs even in the vanadium spectrum, but L series analysis is possible from silver onwards. In krypton, the K spectra of the elements up to selenium are free of irregularities, but from rubidium onwards a distinct krypton loss peak occurs. The xenon loss peak is very small in xenon filled tubes, which are therefore highly suitable for K series analyses on elements up to Cs, and L series analyses thereafter. The following were also determined for all the counter tubes: the dependence of the pulse height on the working voltage; the dependence of the duration of the pulse

Carv 2/3

S/048/63/027/003/023/025
B106/B238

An attempt to use ...

on the load resistance; the dependence of the resolution on the working voltage, i. e. the gas amplification factor, and on the load resistance. The resolution is practically independent of the working voltage when this is near 400 v for type 1 counters or 150 v for type 2 counters. The characteristics of these counters does not change in course of two years operation. There are 13 figures.

Card 3/3

4554. RAPID METHOD FOR DETERMINING HYDROGEN SULPHIDE AND PHOSPHINE
IN ACETYLENE. Perel'man, S. S. and Lefyukina, T. M. (Zavodskaya Lab.,
1945, 11, 810-11; Chem. Abstr., 1947, 41, 1176).

Pass the gas through NaOCl solution to absorb H_2S and PH_3 by
oxidation to H_2SO_4 and H_3PO_4 . To the resulting solution add 5 ml.
of 6 N. HCl, evaporate to dryness, take up the residue in water, and
transfer to a 200-ml. volumetric flask. To an aliquot part, add acid
molybdate reagent and reduce the resulting phosphomolybdate to Mo
blue by adding 5 ml. of solution prepared from 90 g. $MnSO_4 \cdot 7H_2O$ +
2 g. hydroquinone per l. compare with a standard in a Duboseq colori-
meter after 30 min. In another aliquot determine the H_2SO_4 by
precipitating it as $BaSO_4$ with a measured volume of 0.01 N. $BaCl_2$
solution, filtering off the $BaSO_4$, precipitating the excess Ba^{+2} with
a measured volume of 0.015 N. $K_2Cr_2O_7$ solution + H_2O , filtering off
the $BaCrO_4$ precipitate, and measuring the excess Cr^{+6} by the
diphenylarsazide reaction in dilute H_2SO_4 , eventually measuring the
colour in a colorimeter.

4-I-8

BC

Production of thermo-phosphates from Khabinsk
 apatite. R. I. VOLSKOVAN and S. B. POKHMAN (Udsk.
 Uralsk, 1980, 2, 590-593). Fluorapatite afforded a pro-
 duct containing 40-50% P_2O_5 ; this was heated for
 30 min. at 1200° with 40% of $MgCO_3$. Optimal condi-
 tions for other samples (57/22, 19-47% P_2O_5) were also
 determined. Addition of SiO_2 (20%) or CaO slightly
 increased the amount of decomp. The fertilizer value of
 thermo-phosphate is equal to that of Thomas slag, but
 slightly inferior to that of superphosphate.
 CHEMICAL ABSTRACTS.

ASAP-11A METALLURGICAL LITERATURE CLASSIFICATION

FROM DIVISION	ISSUED MAY 1981	COLLECTION	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100																	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100

PERELMAN, S. S.
D. S. DOROFEEV, Trans. Sci. Inst. Fertilizers (USSR) No. 101,
62-73, 1933

157


ca

Decomposition of phosphorite with hydrochloric acid and with mixtures of hydrochloric acid, sulfuric acid and ammonium chloride. S. I. VOLPROVICH AND S. S. PASMANOVA. *Zhurnal Prikladnoi Khim.* 1938, 11, 118; cf. C. A. 23, 2507. — Wyatka phosphorite, contg. 26.7% P_2O_5 , 5.1% CO_2 , 4.5% $(Al, Fe)_2O_3$, yielded HCl exts. with 8-9% P_2O_5 . 2.04 parts 26.6% HCl decompose 95-96% of the mineral. The optimal HCl concn. is 26%. The exts. contain 0.5-0.8% mesquite which were extd. up to 21-40% from the mineral. A mixt. of HCl and H_2SO_4 acts with the same good result. Addn. of NH_4Cl decreases the rate of decompn. ALFRED BURCAS

ASD-51A METALLURGICAL LITERATURE CLASSIFICATION

SECTION	SUBSECTION	CLASSIFICATION
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8
9	9	9
10	10	10
11	11	11
12	12	12
13	13	13
14	14	14
15	15	15
16	16	16
17	17	17
18	18	18
19	19	19
20	20	20
21	21	21
22	22	22
23	23	23
24	24	24
25	25	25
26	26	26
27	27	27
28	28	28
29	29	29
30	30	30
31	31	31
32	32	32
33	33	33
34	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39
40	40	40
41	41	41
42	42	42
43	43	43
44	44	44
45	45	45
46	46	46
47	47	47
48	48	48
49	49	49
50	50	50
51	51	51
52	52	52
53	53	53
54	54	54
55	55	55
56	56	56
57	57	57
58	58	58
59	59	59
60	60	60
61	61	61
62	62	62
63	63	63
64	64	64
65	65	65
66	66	66
67	67	67
68	68	68
69	69	69
70	70	70
71	71	71
72	72	72
73	73	73
74	74	74
75	75	75
76	76	76
77	77	77
78	78	78
79	79	79
80	80	80
81	81	81
82	82	82
83	83	83
84	84	84
85	85	85
86	86	86
87	87	87
88	88	88
89	89	89
90	90	90
91	91	91
92	92	92
93	93	93
94	94	94
95	95	95
96	96	96
97	97	97
98	98	98
99	99	99
100	100	100

1ST AND 2ND CODES		PROCESS AND PROPERTY CODES		3RD AND 4TH CODES	
<p><i>CO</i> <i>15</i></p> <p>Experiments on the production of thermophosphates from the Khibinsk apatite. S. I. VOLZHOVICH AND S. S. FRASLMAN. <i>Udolezhenie Urashei (Fertilizers and Crops)</i> 2, 570-594 (1930).—By a Goldschmidt method a product was obtained from the Khibinsk apatite with a 40.5% P_2O_5 content. This and 2 other samples contg. 27.12 and 19.47% P_2O_5 were fused with Na_2CO_3. By using 30.2 parts of the 40.5% P_2O_5 sample for 100 parts of the phosphate at 900–1200° a product was obtained with a 70% coeff. of decarbox., the latter representing the ratio of citrate-sol. P_2O_5 to the total. With a 25% excess of Na_2CO_3 the coeff. increases irrespective of the temp. from 900° to 1200°. With a 50% increase the proportionality between the Na_2CO_3 and increase in P_2O_5 disappears. At 1100° the coeff. drops from 75.3 to 60.7% and then again increases at 1200° to 93.6%. At 1200° the mixt. fuses, but there is no increase in P_2O_5. The optimum conditions were found to be at 1200° with 1.5 times the amt. of soda used originally, i. e., 45 parts of Na_2CO_3 to 100 parts of apatite. With the 27.1% P_2O_5 sample at 1000–1200° with 20 parts of Na_2CO_3 to 100 parts of phosphate the coeff. of decarbox. was 70–80%. A 25% increase of Na_2CO_3 increased the coeff. of decarbox. almost to 100%. Even at 900° such a mixt. gave an 83.2% coeff. With the 19.5% P_2O_5 sample at 1200° with 22 parts of Na_2CO_3 to 100 parts of the phosphate almost 100% of the phosphate became citrate sol. Addns. of 10% SiO_2 to the mixt. slightly increased the coeff. of decarbox. SiO_2 alone had no effect. An increase of the SiO_2 to 20% produced neg. results. Addns. of $CaCO_3$ alone had no effect, but with the Na_2CO_3 an increase in the coeff. took place. The time factor of heating the mixt. brought out the fact that 30 min. gives the optimum. The cooling of the mixt. immediately after 30 min. heating increased the soly. of the product. Heating with various chlorides gave neg. results. With Na_2SO_4 and charcoal a product was obtained with a coeff. of 80%. Vegetation expts. with thermophosphates show that it is just as good as Thomas slag, but it is slightly inferior to superphosphate.</p> <p style="text-align: right;">J. S. JORNA</p>					
<p>ASB-51A METALLURGICAL LITERATURE CLASSIFICATION</p>					
<p>FROM SYNONYMS</p>					
<p>SYNONYMS</p>					
<p>SYNONYMS</p>					
<p>SYNONYMS</p>					



The preparation of dicalcium phosphate from phosphorite. S. S. FERNLEY
 AND I. N. NIKONOVA. *J. Chem. Ind. (Moscow)* 1932, No. 12, 214. Crude CaHPO_4
 from phosphorite is treated with Ca(OH)_2 at pH 2.4. Fe and Al ppt. as phosphates
 and F as CaF_2 . After filtration, the soln. is neutralized, and almost pure $\text{CaHPO}_4 \cdot 2\text{H}_2\text{O}$
 ppts. Slight amts. of As remain in soln. The CaHPO_4 thus obtained is cheap and can
 be used for animal feeding. H. M. LICKSTON

ADD-51-A METALLURGICAL LITERATURE CLASSIFICATION

18

CA

Analysis of gases and determination of the degree of absorption in nitric acid systems. S. S. Petrl'man and V. I. Tikhonov. Zhuravskiy Lab. 11, 905-10(1945). Equations are derived to calc. the degree of absorption of N oxides in each column of HNO₃ systems or in any part of the absorption system. It is also possible to det. the quantity of N oxides in the condensate if the system. W. R. Henn

1ST AND 2ND COLUMNS

PROPERTIES AND PROPERTIES INDEX

COMP. ELEMENTS

ASD. SEA METALLURGICAL LITERATURE CLASSIFICATION

1ST AND 2ND COLUMNS

3RD AND 4TH COLUMNS

5TH AND 6TH COLUMNS

7TH AND 8TH COLUMNS

9TH AND 10TH COLUMNS

11TH AND 12TH COLUMNS

13TH AND 14TH COLUMNS

15TH AND 16TH COLUMNS

17TH AND 18TH COLUMNS

19TH AND 20TH COLUMNS

21TH AND 22TH COLUMNS

23TH AND 24TH COLUMNS

25TH AND 26TH COLUMNS

27TH AND 28TH COLUMNS

29TH AND 30TH COLUMNS

31TH AND 32TH COLUMNS

33TH AND 34TH COLUMNS

35TH AND 36TH COLUMNS

37TH AND 38TH COLUMNS

39TH AND 40TH COLUMNS

41TH AND 42TH COLUMNS

43TH AND 44TH COLUMNS

45TH AND 46TH COLUMNS

47TH AND 48TH COLUMNS

49TH AND 50TH COLUMNS

51TH AND 52TH COLUMNS

53TH AND 54TH COLUMNS

55TH AND 56TH COLUMNS

57TH AND 58TH COLUMNS

59TH AND 60TH COLUMNS

61TH AND 62TH COLUMNS

63TH AND 64TH COLUMNS

65TH AND 66TH COLUMNS

67TH AND 68TH COLUMNS

69TH AND 70TH COLUMNS

71TH AND 72TH COLUMNS

73TH AND 74TH COLUMNS

75TH AND 76TH COLUMNS

77TH AND 78TH COLUMNS

79TH AND 80TH COLUMNS

81TH AND 82TH COLUMNS

83TH AND 84TH COLUMNS

85TH AND 86TH COLUMNS

87TH AND 88TH COLUMNS

89TH AND 90TH COLUMNS

91TH AND 92TH COLUMNS

93TH AND 94TH COLUMNS

95TH AND 96TH COLUMNS

97TH AND 98TH COLUMNS

99TH AND 100TH COLUMNS

PZREL'MAN, S.T.

Open-hearth furnace or oxygen converter? Stal' 22 no.2:124-125
F '62. Stal' 22 no.2:124-125 F '62. (MIRA 15:2)
(Steel---Metallurgy)

a-1

RC

Influence of inert additions on the lower limit of the photochemical explosion of the $H_2 + Cl_2$ mixture. F. A. LAVROV and T. FRANKMAN (Akts. Fizicokhim. U.S.S.R., 1955, 2, 61-102).—The influence of excess of H_2 or Cl_2 and additions of N_2 , A , CO_2 , and HCl on the lower explosion pressure P_{min} of stoichiometric $H_2 + Cl_2$ mixtures has been studied. P_{min} is a min. at 70% Cl_2 and then increases linearly with the pressure of added gas in accordance with a theoretical equation. Assuming equal deactivation probabilities s in each case, the ratio addition concn./ $[N_2]$ for a given P has been calc. and good agreement obtained with experimental ratios, except in the case of HCl , when $s_{HCl} = 2.2s_{N_2}$. It is supposed that HCl becomes excited and may then activate another Cl_2 . The occurrence of P_{min} at 70% Cl_2 is ascribed to excited Cl_2 in the rôle of chain carrier. R. S.


ASB-56A METALLURGICAL LITERATURE CLASSIFICATION

FROM SYMBOLS

EXPOSED MAP ONLY ONE

COLLECTIONS

EXPOSED MAP ONLY ONE



1ST AND 2ND LETTERS																										3RD AND 4TH LETTERS																									
PROCESS AND PROPERTIES INDEX																																																			
C A																										3																									
<p>The manufacture and use of the photoelectric step spectrophotometer. V. A. Sukhikh and T. B. Perelman. <i>Lekhsya Prom.</i> 17, 132 (1958); <i>Chem. Abstr.</i> 1959, II, 2469. -- A spectrophotometer is described which operates with 2 Sr cells in differential connection. The instrument is recommended for use in the dye industry. Reference is made to appropriate literature. M. G. Moore</p>																																																			
<p>ASM-SEA METALLURGICAL LITERATURE CLASSIFICATION</p>																																																			
<p>1ST AND 2ND LETTERS 3RD AND 4TH LETTERS</p>																																																			

BC

Preparation of colored filters. V. A. BOGOMOL
and T. B. FINKELMAN (Kavod. Lab., 1937, G. 730—
730).—The filters are prepared by spraying dye
solutions on to glass surfaces. H. T.


11-1

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

FROM SOURCE

CLASSIFY ONE ONLY

CLASSIFY ONE ONLY



85437

S/170/60/003/011/008/016
B019/B056

11.9200
AUTHOR:

Perel'man, T. L.

TITLE:

The Temperature Distribution in a Cylinder With Internal
Heat Sources and Its Cooling by a Turbulent Liquid Flow

PERIODICAL:

Inzhenerno-fizicheskiy zhurnal, 1960, Vol. 3, No. 11,
pp. 72-76

TEXT: In the case of high liquid velocities and a small thickness of the boundary layer, it may be approximately assumed for the zone of the steady flow that the quantity of heat transferred from the heated cylinder is used for heating the center of the liquid flow. For this simplification, the heat exchange differential equations may be written down in the following manner:

$$c_0 \frac{\partial t(r, z, \tau)}{\partial \tau} = \lambda \left\{ \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial t(r, z, \tau)}{\partial r} \right) + \frac{\partial^2 t(r, z, \tau)}{\partial z^2} \right\} + Q(r, z, \tau) \quad (1)$$

$$c_{\text{liqu}} \frac{\partial t_{\text{liqu}}(z, \tau)}{\partial \tau} + v \frac{\partial t_{\text{liqu}}}{\partial z} = \alpha \frac{P}{S_{\text{liqu}}} [t(z, R, \tau) - t_{\text{liqu}}(z, \tau)] \quad (2)$$

Card 1/2

85437

The Temperature Distribution in a Cylinder S/170/60/003/011/008/016
With Internal Heat Sources and Its Cooling B019/B056
by a Turbulent Liquid Flow

In the present paper, an exact solution of this system is obtained. The boundary- and initial conditions are given. This system is transformed into a system of two linear integral equations by means of a Laplace transform. The latter are transformed into a linear Fredholm equation of second kind and solved in the usual manner. A detailed investigation of the solution will be given in a later paper. The author thanks Academician A. V. Lykov for discussing the results obtained. There are 2 Soviet references.

ASSOCIATION: Institut energetiki AN BSSR, g. Minsk
 (Institute of Power Engineering of the AS BSSR, Minsk)

SUBMITTED: April 11, 1960

Card 2/2

S/170/60/003/005/016/017
B012/B056

AUTHOR: Perel'man, T. L.

TITLE: The Temperature Field in a Finite Cylinder With Inner
Sources *20*

PERIODICAL: Inzhenerno-fizicheskiy zhurnal, 1960, Vol. 3, No. 5, *✓c*
pp. 138-144

TEXT: First, the equation (1) of thermal conductivity for the problem with cylinder symmetry and a density Q of the heat sources is written down. One front side of the cylinder is assumed to be heat-insulated, whereas the temperature of the other front side is constant and equal to the temperature of the medium surrounding the cylinder. Formula (2) is written down for the convective heat exchange occurring in all cases on the cylinder jacket. New variables are introduced, and (1) and (2) are transformed into formulas (4) and (5). Equation (4) is solved under the conditions (5), and a differential equation of the first order is obtained. By using the integral transformation, formula (6) is finally obtained for temperature. From this formula there results the solution of the problem for

Card 1/2

The Temperature Field in a Finite Cylinder
With Inner Sources

S/170/60/003/005/016/017
B012/B056

a finite cylinder with arbitrary source density under the boundary conditions (2). A special case is then investigated, in which the heat source density has the form of equation (10). For this case, formula (12) is obtained for temperature. In conclusion, the results are given for some simple boundary conditions at the front sides of the cylinder, which differ from the boundary condition (5b). Academician A. V. Lykov and the author discussed the results obtained by this investigation. The results are of interest for the study of heat transfer in nuclear reactors. There are 5 Soviet references. ✓c

ASSOCIATION: Institut energetiki AN BSSR, g. Minsk
(Institute of Power Engineering of the AS BSSR, Minsk)

Card 2/2

S/170/60/003/010/022/023
B019/B054

AUTHORS: Yermakov, V. S., Perel'man, T. L.

TITLE: Problems of Nuclear Physics (II All-Union Conference on Low- and Medium-energy Nuclear Reactions)

PERIODICAL: Inzhenerno-fizicheskiy zhurnal. 1960, Vol. 3, No. 10, pp. 139-143

TEXT: The II Vsesoyuznaya konferentsiya po yadernym reaktsiyam pri malykh i srednikh energiyakh (II All-Union Conference on Low- and Medium-energy Nuclear Reactions) was organized in Moscow by the AS USSR on July 21-28, 1960. I. M. Frank, Corresponding Member of the AS USSR, headed the organizing committee. In his opening speech, he pointed out that the investigation of low-energy nuclear reactions quite naturally deals with the problems of nuclear structure. N. A. Vlasov gave a survey of experimental investigations of systems containing less than eight nucleons in the nucleus. Among other things, this report dealt with the existence of a tetra-neutron, the isotope H^8 , and some hydrogen isotopes, as predicted by Ya. B. Zel'dovich, V. I. Gol'danskiy, and A. I. Baz'. A. I. Baz' ✓

Card 1/3

Problems of Nuclear Physics (II All-Union
Conference on Low- and Medium-energy Nuclear
Reactions)

S/170/60/003/010/022/023
B019/B054

gave a survey of theoretical investigations of these systems. He mentions the investigation of the three-particle problem for short-range forces carried out by G. V. Skornikov and K. A. Ter-Martirosyan (Ref. p. 140). L. D. Landau made some critical remarks during the subsequent discussion, mainly on missing levels in one of the mirror nuclei. Further, Ya. B. Zel'dovich stated that the existence of H^8 is very likely. V. I. Gol'danskiy suggested the hypothetical reaction $Be^9(\pi^+, p)He^8$ for the experimental proof of the existence of H^8 . I. S. Shapiro showed in his report that the π -meson capture does not only supply information on elementary particles, but also on the structure of light nuclei. A. A. Ogloblin and V. G. Neudachin gave a survey of experimental and theoretical investigations on direct interactions of nuclei. A. P. Klyucharev (Khar'kov) spoke about elastic proton scattering. P. E. Nemirovskiy dealt with inelastic nucleon scattering. In the discussion of this report A. S. Davydov discussed the use of the optical model for light nuclei. I. Kh. Lemberg reported on investigations of the Coulomb excitation of nuclear levels by multiply charged ions. These investigations were carried out at the Leningradskiy fiziko-tekhnicheskii institut AN SSSR (Leningrad)

Card 2/3

Problems of Nuclear Physics (II All-Union
Conference on Low- and Medium-energy Nuclear
Reactions)

S/170/60/003/010/022/023
B019/B054

Institute of Physics and Technology of the AS USSR). In the discussion of this report, experimental results obtained in Dubna were given on the excitation of rotational levels by μ -mesonic transitions of U^{238} atoms. V. I. Gol'danskiy reported on the possibility of a two-proton activity of some nuclei. In an attempt made to explain theoretically the results obtained by Almquist, A. S. Kompaneys suggested the model of a two-nucleus quasimolecule $C^{12}-C^{12}$. A. I. Baz' reported on his calculations of a nuclear molecule model. L. D. Landau and A. I. Alikhanov took part in the discussion of R. Moessbauer's report. F. L. Shapiro gave a survey of experimental and theoretical investigations of the resonance scattering of γ -quanta carried out by A. I. Alikhanov et al. Investigations carried out at the FIAN and MGU are also considered. L. Ye. Lazarev and A. M. Baldin reported on experimental investigations of photonuclear reactions. L. V. Groshev and S. P. Tsytko on the radiation capture of nucleons. A. S. Davydov reported on non-axially symmetric nuclei, Yu. T. Grin on the superfluidity of nuclear substance which he had discovered together with A. B. Migdal. Reports delivered by American, Canadian, British, German, and Italian scientists are also discussed. There is 1 Soviet reference. ✓

Card 3/3

PERELMAN, T.I.

Temperature fields in a finite cylinder with internal sources of heat and a cooling glow of liquid. Dokl. AN BSSR 4 no. 4:156-159 (MIRA 13:10)
Ap '60.

1. Institut energetiki AN BSSR. Predstavleno akad. AN BSSR A.V. Iglovym.

(Thermodynamics)

PEREL'MAN, T.L.; ATENKOV, S., tekhn. red.

[Heat transfer in a laminar boundary layer during flow over a thin plate containing internal sources; Conference on Heat and Mass Transfer, Minsk, 1961] Teploobmen v laminarnom pogranichnom sloye pri obtekanii tonkoi plastiny s vnutrennimi istochnikami; soveshchanie po teplo-i massoobmemu, g. Minsk, 1961 g. Minsk, 1961. 9 p. (MIRA 15:2)
(Heat—Transmission) (Laminar flow) (Boundary layer)

PEREL'MAN, T. L.

" Conjugate tasks of heat-exchange."

Report presented at the 1st All-Union Conference on Heat- and Mass-
Exchange, Minsk, BSSR, 5-9 June 1961.

FEREL'MAN, T. L. and ANTISIMOV, S. I.

"Diffusion of charged particle in the presence of recombination."

Report presented at the 1st All-Union Conference on Heat- and Mass Exchange,
Minsk, BSSR, 5-9 June 1961

21776

S/170/61/004/004/007/014
B108/B209

11.4200

AUTHOR: Perel'man, T. L.

TITLE: The heat exchange in a laminar flow through a tube

PERIODICAL: Inzhenerno-fizicheskiy zhurnal, v. 4, no. 4, 1961, 43 - 48

TEXT: The author presents the combined solution of the heat conduction equations of a liquid flowing through a tube and of the wall of this tube. The study chiefly concerns the entrance region of a tube of radius R and wall thickness h . The Poiseuille velocity profile in the tube,

$u = u_0(1 - r^2/R^2)$ (u_0 - maximum velocity at $r = 0$), is transformed into $u = u_0 \frac{2y}{R}$, which holds for the entrance region. In this case, $y = R - r$ replaces r , with consideration of only $y \ll R$. With the temperatures of the liquid and of the wall, $\theta(x,y)$ and $t(x,y)$, respectively, the following is the boundary problem:

$$\frac{2y}{R} u_0 \frac{\partial \theta}{\partial x} = \chi \frac{\partial^2 \theta}{\partial y^2}, \quad 0 \leq x < \infty, \quad 0 \leq y < \infty \quad \left(\chi = \frac{k_l}{c_p \rho_l} \right). \quad (1)$$

Card 1/7

21776
S/170/61/004/004/007/014
B108/B209

The heat exchange in a ...

$$\frac{\partial^2 t}{\partial x^2} + \frac{\partial^2 t}{\partial y^2} = 0, \quad 0 \leq x < \infty, \quad -h \leq y \leq 0, \quad (2)$$

$$\eta|_{y \rightarrow +0} = t|_{y \rightarrow -0}, \quad (3)$$

$$-k_f \frac{\partial \eta}{\partial y} \Big|_{y \rightarrow +0} = -k_s \frac{\partial t}{\partial y} \Big|_{y \rightarrow -0}, \quad (4)$$

$$\eta|_{x=0} = 0, \quad (5)$$

$$\eta|_{y \rightarrow -\infty} = 0. \quad (5')$$

$$t|_{y \rightarrow -h} = t_0. \quad (6)$$

$$\frac{\partial t}{\partial x} \Big|_{x=0} = 0. \quad (7)$$

Card 2/7

21776

S/170/61/004/004/007/014
B108/B209

The heat exchange in a ...

For the solution of this system, the author introduces the new variable

$$z = \frac{2}{3} \frac{y^{1/2}}{\tau^{1/2}} \left(\tau = \frac{\chi R}{2u_0} \right), \quad (8)$$

into Eq. (1). With this substitution the expression

$$\theta(x) = b \int_0^x \frac{p(y)}{(x-y)^{1/2}} dy. \quad (16)$$

is obtained for the temperature of the liquid at the wall. In this expression, $b = \beta / 2^{1/3} - (2/3)$ and $p(x)$ a function that originates from the condition (4) after substitution of (8): $-p(x) = \frac{\partial t}{\partial y} \Big|_{y=0}$. The solution of Eq. (2) has the form

Card 3/7

21776

S/170/61/004/004/007/014
B108/B209

The heat exchange in a ...

$$t(x, y) = t_0 - \frac{2}{\pi} \int_0^{\infty} \frac{\operatorname{sh} a(h+y)}{\operatorname{ch} ah} \frac{\cos ax}{a} p_c(a) da, \quad (17)$$

where

$$p_c(a) = \int_0^{\infty} p(x) \cos ax dx.$$

Accordingly, the temperature within the tube is

$$\theta(x) = t_0 - \frac{1}{\pi} \int_0^{\infty} \ln \left[\operatorname{cth} \frac{\pi(x+y)}{4h} \operatorname{cth} \frac{\pi|x-y|}{4h} \right] p(y) dy. \quad (18)$$

For $x/h \gg 1$ (far from the wall) Eq. (18) assumes, after some transformations, the form $\theta(x) \approx t_0 - hp(x)$. From this equation and Eq. (16), the second-kind Volterra integral equation is obtained for $p(x)$;

Card 4/7

21776
S/170/61/004/004/007/014
B108/B209

The heat exchange in a ...

$$p(x) = \frac{t_0}{h} F(\xi), \quad (20)$$

$$\theta(x) = t_0 [1 - F(\xi)], \quad (21)$$

$$F(\xi) = \frac{3\sqrt{3}}{2\pi} \int_0^\infty \frac{e^{-\xi z}}{z^2 + z + 1} dz, \quad (22)$$

where ξ is a dimensionless parameter:

$$\xi = \frac{1}{6} \left[\frac{\Gamma(1/3)}{\Gamma(2/3)} \right]^3 \frac{1}{x^3} \left(\frac{R}{h} \right)^2 \frac{1}{Pe} \frac{x}{h}; \quad (23)$$

Pe is the Peclet number, equaling the product of Reynold's and Prandtl's number. For not too great ξ , Table 1 gives the values of the integral (22). For great ξ ,

Card 5/7

21776

S/170/61/004/004/007/014
B108/B209

The heat exchange in a ...

$$F(\xi) \sim \frac{\sqrt{3}}{2\pi} \sum_{n=0}^{\infty} a_n \Gamma\left(\frac{n+1}{3}\right) \frac{1}{\xi^{\frac{n+1}{3}}} \quad (24),$$

where a_n is determined from $\bar{\phi}(z) = \sum_{n=0}^{\infty} a_n z^n$; $\bar{\phi}(z) = \frac{1}{z^2 + z + 1}$;
 ($a_0 = 1, a_1 = -1, a_2 = 0, a_3 = 1, \dots$). The coefficient of local heat exchange and the local Nusselt number are given by

$$\alpha = k_s \frac{p(x)}{\theta(x)}, \quad (25)$$

$$Nu_x = \frac{1}{x} \frac{p(x)}{\theta(x)} x, \quad (25').$$

The conditions for the validity of the solutions are 1) $x/h \gg 1$; 2) $50 < Pe \frac{R}{x} < 2500$. There are 1 table and 11 references: 4 Soviet-bloc and 7 non-Soviet-bloc.

Card 6/7

21776
S/170/61/004/004/007/014
B108/B209

The heat exchange in a ...

ASSOCIATION: Institut energetiki AN BSSR, g. Minsk
(Institute of Power Engineering AS BSSR, Minsk)

SUBMITTED: February 6, 1961

Таблица 1

ξ	$F(\xi)$	ξ	$F(\xi)$	ξ	$F(\xi)$	ξ	$F(\xi)$
0	1,0000	0,5	0,5131	1,0	0,4517	2,0	0,3921
0,1	0,6475	0,6	0,4887	1,2	0,4367	2,5	0,3809
0,2	0,5896	0,7	0,4826	1,4	0,4229	3,0	0,3599
0,3	0,5564	0,8	0,4703	1,6	0,4115	4,0	0,3293
0,4	0,5301	0,9	0,4608	1,8	0,4025	10,0	0,2719

Table 1

Card 7/7

228211

S/170/61/004/005/007/015
B104/B205

26.2181

AUTHOR:

Perel'man, T. L.

TITLE:

Heat exchange in a laminar boundary layer flowing round thin plates with internal sources of heat

PERIODICAL: Inzhenerno-fizicheskii zhurnal, v. 4, no. 5, 1961, 54-61

TEXT: The system of equations describing the present problem (Fig. 1) reads:

$$u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} = \nu \frac{\partial^2 u}{\partial y^2}, \quad \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0, \quad (1)$$

The boundary conditions are: $u|_{y=0} = v|_{y=0} = 0$, $u|_{y=\infty} = U$ (2). For the temperature of the liquid one finds $u \partial \theta / \partial x + v \partial \theta / \partial y = \chi \partial^2 \theta / \partial y^2$ (3), where a) $\theta|_{x=0} = 0$ and b) $\theta|_{y=\infty} = 0$ are the boundary conditions. The equation $\partial^2 t / \partial x^2 + \partial^2 t / \partial y^2 = -Q(x, y) / k_s$ (5) holds for the plate. In these equations, t and θ denote the temperatures of the plate and the liquid, respectively. The author confines himself to a finite power of the heat

Card 1/4

22821.

S/170/61/004/005/007/015
B104/B205

Heat exchange in a laminar boundary...

sources ($\int Q(x,y)dV < \infty$). Under the boundary conditions (?), Eqs. (1) have the well-known exact solutions of H. Blasius (Z. Math. Phys., 56, 1, 1908). By introducing the variable $\eta = (y/2)\sqrt{U/\nu x}$, this system can be reduced to the differential equation $\eta^3 f/d\eta^3 + \eta f d^2 f/d\eta^2 = 0$ (13) with the boundary conditions $f(0) = f'(0) = 0$ and $f'(\infty) = 2$. $\psi = \sqrt{\nu U x} f$, where ψ is the stream function. Eq. (13) can be solved either numerically or by expansion in a power series of η . The differential equation (3) is solved on the basis of publications by L. I. Sedov (Metody podobiya i razmerrosti v mekhanike, GMITL, 1957), V. G. Levich (Fiziko-khimicheskaya gidrodinamika, Fizmatgiz, 1959), and Sutton W. (Proc. Roy. Soc., 182, 48, 1943). One obtains

$$\theta(x) = \gamma \int_0^x \frac{p(y)}{(x^2 - y^2)^{1/2}} dy, \quad (24), \quad \text{where } \gamma = \frac{2\tau}{4\Gamma(1/3)b\beta^{1/2}},$$

$a = 3/4\Gamma(2/3)\beta^{2/3}$, $b = 3^{5/3}/8\lambda x\Gamma(1/3)\beta^{1/3}$. The solution to Eq. (5) reads

Card 2/4

22821,

Heat exchange in a laminar boundary...

S/170/61/004/005/007/015
B104/B205

$$\theta(x) = \frac{Q_0}{k_s} x \left(1 - \frac{x}{2}\right) + \frac{Q_0}{k_s} \frac{l^2}{2} (x-l) - \frac{1}{h} \int_0^x G(x,y) p(y) dy - \frac{1}{\pi} \int_0^x \ln \left[\frac{1 - e^{-\frac{x+y}{h}}}{1 - e^{-\frac{x-y}{h}}} \right] p(y) dy, \quad (25)$$

where $G(x,y) = \begin{cases} y & \text{for } y < x \\ x & \text{for } y > x \end{cases}$. Thus, the problem is reduced to the solution of the integral equations (24) and (25). The author confines himself to $x/h \gg 1$ and is thus able to simplify Eq. (25) considerably. The expressions obtained for the unknown functions $\theta(x)$ and $p(x)$ are used to determine $\theta(x,y)$ and $t(x,y)$ in quadratures. There are 1 figure and 10 references: 6 Soviet-bloc and 4 non-Soviet-bloc. The most important reference to the English-language publication reads as follows: Chapman D. R., and Rubesin M. W., J. Aeronaut. Sci., 16, 547, 1949.

ASSOCIATION: Institut energetiki AN BSSR, g. Minsk (Institute of Power Engineering, AS BSSR, Minsk)

Card 3/4

PEREL'MAN, T.L.

One boundary value problem for equations of a mixed type in
the theory of heat conduction. Inzh.fiz.zhur. 4 no.8:121-125
Ag '61. (MIRA 14:8)

1. Institut energetiki AN BSSR, Minsk.
(Boundary value problems) (Heat--Conduction)
(Differential equations, Partial)

16. 4500

S/044/62/000/008/027/073
C111/C333

AUTHOR: Perel'man, T. L.

TITLE: On the asymptotic solutions for a class of integral equations

PERIODICAL: Referativnyy zhurnal, Matematika, no. 8, 1962, 57-58, abstract 8B259. ("Dokl. An BSSR", 1961, 2, no. 12, 538-540).

TEXT: A method is described for the equation

$$a(x)\varphi(x) = g(x) + \int_0^{\infty} k\left(\frac{x}{y}\right) x^{\alpha} y^{\beta} \varphi(y) dy$$

where $a(x) = \sum_{k=1}^n a_k x^{\sigma_k}$, according to which one can obtain the

asymptotic solution with large x in a number of cases. The method is based on the Mellin transformation, on the representation of the unknown function $\phi(s+\delta) = \Omega(s)\Psi(s)$ and on the corresponding choice of the factor $\Omega(s)$.

[Abstracter's note: Complete translation.]

Card 1/1

16.4500 16.6500 16.4100

²¹³⁵²
S/040/61/025/006/021/021
D299/D304

AUTHOR: Perel'man, T.L. (Moscow)

TITLE: On asymptotic expansion of the solutions of a class of integral equations

PERIODICAL: Prikladnaya matematika i mekhanika, v. 25, no. 6, 1961, 1145 - 1147

TEXT: Various problems of mathematical physics involve the solution of singular integral equations of type

$$a(x) \varphi(x) = f(x) + \int_0^{\infty} k\left(\frac{x}{y}\right) x^{\alpha} y^{\beta} \varphi(y) dy \quad (1) \quad 4$$

where
$$a(x) = \sum_k a_k x^{\gamma_k} \quad (a_k = \text{const}). \quad (2)$$

The asymptotic expansion has the form

Card 1/4

On asymptotic expansion of the ...

21352
S/040/61/025/006/021/021
D299/D304

Recursion relations for the coefficients c_n and the constants a and b are found from the equation

$$\sum_k a_k \Omega(s + \gamma_k - \delta) \Psi(s + \gamma_k - \delta) = F(s) + G(s) \Psi(s + \alpha + \beta - \delta + 1), \quad (7)$$

where $G(s) = K(s + \alpha) \Omega(s + \alpha + \beta - \delta + 1). \quad (8)$

Thereupon, the sought-for function $\Phi(x)$ can be readily found by means of Eq. (6). The relation between the functions $\Omega(s)$, $G(s)$ and $\Psi(s)$ is such, that the solution $\Phi(x)$ is uniquely determined. For integral equations met in practice, the function $\Omega(s)$ with the necessary analytical properties, can be readily constructed. It is noted that the above argument can be extended, without substantial modifications, to broader classes of equations than Eq. (1). Thus $a(x)$ may be a linear differential operator (i.e. Eq. (1) can be also an integro-differential equation). Also other types of kernels are admissible. As an example, the integral equation

Card 3/4

08404

S/020/61/136/004/012/026
B019/B056

9.9600 (also 1143, 1482)

AUTHOR: Perel'man, T.L., and Anisimov, S.I.

TITLE: Density Distribution of Charged Particles in Meteor Tracks

PERIODICAL: Doklady Akademii nauk SSSR, 1961, Vol. 136, No. 4, pp. 810-812

TEXT: For the purpose of studying the reflection of radiowaves from meteor tracks it is necessary to know the density distribution of charged particles. By diffusion, recombination, and addition of electrons to neutral atoms and molecules, density changes, the latter effect not changing the density distribution, but the effective recombination coefficient. The relative effect of recombination and diffusion upon the density distribution may be expressed by the dimensionless parameter $\xi = \alpha q/D$, where α is the recombination coefficient, q the number of ionizations per unit length of the meteor track, and D the diffusion coefficient. A differential equation is given, which describes the density of charged particles produced by a meteor moving with uniform speed: X

Card 1/3

88404

Density Distribution of Charged Particles
in Meteor Tracks

S/020/61/136/004/012/026
B019/B056

$$\partial n / \partial t = D \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial n}{\partial r} \right) - \alpha n^2 + \frac{q}{2\pi v} g \left(\frac{r}{r_0} \right) \delta(z - vt) \quad (2)$$

$$n(0, t) < \infty, \quad n(\infty, t) = 0 \quad (3)$$

This differential equation may be calculated by means of the perturbation theory in the case of small ξ . With ξ being greater, the perturbation theory is not applicable, and an approximation has to be found. The authors discuss the two methods of solution and obtain expressions describing the time dependence of the number of charged particles. They thank Academician Ya.B. Zel'dovich for valuable advice, as well as Member of the AS BSSR M.A. Yel'yashevich, G.L. Barenblatt und Yu.P. Rayzer for discussions. There are 3 references: 2 Soviet and 1 US.

ASSOCIATION: Institut fiziki Akademii nauk BSSR
(Institute of Physics, Academy of Sciences BSSR)
PRESENTED: September 1, 1960, by Ya.B. Zel'dovich, Academician
Card 2/3